MAT3 High capacity yarn accumulator

The MAT3 enables to accumulate a high quantity of yarns between the heat-setting line exit and the winder, so that the bobbin-doffing at the time of the take-up might take place without stopping the line. This accumulation enables the treatment of delicate fibres that would not admit a too long stopping inside the steaming chamber, and also allows a better bundle separation thus increasing efficiency by eliminating yarn breaks.

- > Constant density for a better yarn bundle separation with the motorized conveyor belt
- > Virtually no length limitation (extension by 3m steps)
- > Easy threading trolley pneumatic adjustment
- > Yarn tension continuous adjustment by separate controlled feeding (2 inverters)



MAT3 can be installed on the floor or on top of the heat-setting line.

Technical information

MAT3:		
standard delivery = 10,5m	On the floor (*)	On top of the line (*)
Accumulation length (m) (* Add 0,5m to shoot length for trolley)	7m - 10m - 13m extension by 3m steps up to 22m (and more if required)	7m - 10m - 13m - 16m (max.)
Accumulation capacity	10kg of yarn per meter (100Kg for a 10m standard MAT3)	
Accumulation speed	up to 600m/min	
Air consumption	0,1 Nm³/h (6 bars supply)	
Electrical consumption [3ph. 400-500Vac / 50-60Hz]	average 2,5KW/h (installed power 7KVA) depends on yarn type & count	
Dimensions (mm) (example for a 7,5m length MAT3)	L9500 x W800 x H860	

> Do not hesitate to contact our sales team for any question or specific demands



Advanced heat-setting solutions



SUPERBA S.A.S.

147 avenue Robert Schuman 68055 MULHOUSE Cedex

Tel. +33 389 362 727 Fax +33 389 362 773





SUPERBA SHANGHAI



SUPERBA MIDDLE-EAST FZE

MAT3

High capacity yarn accumulator



> Continuous process guarantee

line efficiency





Advanced heat-setting solutions